STP13-30

HAND PUSH HYDRAULIC POWER STATION



FEATURES

- Imported original engine provides sufficient power for hydraulic equipment
- High-quality quick interface, it is more convenient and fast to replace hydraulic tools
- Original imported hydraulic pump, quality assurance, stable performance
- Imported control valve block, maximum guarantee, stable output of flow
- Front double wheels, easy to move
- Steel frame, strong and durable, not easy to damage
- The surface is sprayed with plastic, anti-corrosion and corrosion-resistant, beautiful and generous

Overall size		
Full length	mm	860
Full width	mm	720
Full height	mm	820
Maximum flow	lpm	20-30
Package size	mm	880*775*820

Technical parameter	Unit	STP13-30	
Model		STP13-30	STP13-30C
Engine brand		HONDA/BRIGGS&STRATTON	CHANG CHAI
Engine model		GX390/Pioneer400	192F
Efficiency	hp	13/14	13
Engine type		Gasolinesingle-cylindervertical Four-stroke overhead valve	Air-cooled single-cylinder vertical Four-stroke diesel engine
Maximum flow	lpm	20-30	
Greatest pressure	bar	155	
Rotating speed	rpm	3600	
Weight	kg	148	160
Fuel tank volume	L	6. 5	
Hydraulic tank volume	L	12	
Lubricant quantity	L	1. 1	
Fuel consumption	kg/kwh	313	
Hydraulic circuit		Single hydraulic oil circuit	
Heat dissipation method		Hydraulic oil air cooling and heat dissipation	
Connection method		3/8-inch flat quick connector	
Starting method		Hand start/Electric start	Electric start
Hydraulic oil level gauge		Have	
Overall length	mm	860	
Overall width	mm	720	
Overall height	mm	820	
Packaging size	mm	880*775*820	