# STP18-40

## HAND PUSH HYDRAULIC POWER STATION




## FEATURES

- Imported original engine provides sufficient power for hydraulic equipment
- High-quality quick interface, it is more convenient and fast to replace hydraulic tools
- Original imported hydraulic pump, quality assurance, stable performance
- Imported control valve block, maximum guarantee, stable output of flow
- Front double wheels, easy to move
- Steel frame, strong and durable, not easy to damage
- The surface is sprayed with plastic, anti-corrosion and corrosion-resistant, beautiful and generous

| Overall size | | |
|---|---|---|
| Full length | mm | 950 |
| Full width | mm | 620 |
| Full height | mm | 760 |
| Maximum flow | lpm | 30-40 |
| Package size | mm | 1020*690*830 |

| Technical parameter | Unit | STP18-40 | |
|---|---|---|---|
| Model | | STP18-40 | STP18-40C |
| Engine brand | | BRIGGS&STRATTON(Pioneer) | HUAYUAN KAMA |
| Engine model | | 3564 | KM290F |
| Efficiency | hp | 18 | 18. 3 |
| Engine type | | Double cylinder air-cooled four stroke Horizontal bearing | Dual cylinder inline air-cooled four stroke diesel engine |
| Maximum flow | lpm | 30-40 | |
| Greatest pressure | bar | 155 | |
| Rotating speed | rpm | 3600 | |
| Weight | kg | 146 | 203 |
| Fuel tank volume | L | 21 | |
| Hydraulic tank volume | L | 13 | |
| Lubricant quantity | L | 1. 7 | |
| Fuel consumption | kg/kwh | 313 | |
| Hydraulic circuit | | Single hydraulic oil circuit | |
| Heat dissipation method | | Hydraulic oil air cooling and heat dissipation | |
| Connection method | | 3/8-inch flat quick connector | |
| Starting method | | Electric start | |
| Hydraulic oil level gauge | | Have | |
| Overall length | mm | 950 | 1140 |
| Overall width | mm | 620 | 620 |
| Overall height | mm | 760 | 850 |
| Packaging size | mm | 1020*690*830 | 1250*690*910 |