SMLV1000A/B

Hand propelled mobile lighting vehicle



FEATURES

- Equipped with imported power, quality assurance, superior performance.
- Equipped with metal halide lamp, large luminous flux and long life.
- High performance self-braking hand winch
- 3-section lifting pole, galvanized light pole, anti-drop, corrosion-resistant.
- Left and right windproof support frame, stable support
- Integrated operator panel
- 5 meters lifting height, adjustable irradiation angle, long irradiation distance

Overall size		
Lay down support frame	mm	1585*1740
Pack up support frame	mm	1250*860
Lighthouse Telescopic	mm	1700–5000
Luminous Flux	lm	220000/440000
Power*Number of lights	w	1000*2/1000*4

Technical Parameter	Unit	SMLV1000A/B			
Model		SMLV1000A		SMLV1000B	
Generator set		EC4000CX		EC6500CX	
Gasoline generator		HONDA 3KW		HONDA 5KW	
Diesel generator		ANMAX 3KW		ANMAX 5KW	
Extemal contact power supply		Externally accessible			
Name		Single phase alternator			
Frequency	hz	50			
Rated voltage	V	220			
Maximum power	kva	3. 3		5. 5	
Rated power	kva	3. 2		5	
Continuously working	hr	13		11	
Fuel tank capacity	L	24		25	
Engine weight	kg	71		83	
Headlights		Metal Halide		LED lamp	
Engine size	mm	681*530*571		680*510*540	
Power*Numberof lights	w	1000*2	1000*4	200*2	200*4
Luminous flux	lm	220000	440000	56000	112000
Light stand retractable	mm	1700-5000			
Light stand operation		Three-section lift rod			
Lifting method		Hand lift			
Inclination	°	<10			
Wind resistance		<6			
L*W-Lay down support	mm	1585*1740		1585*1740	
L*W-fold support	mm	1250*860		1250*860	
Way of walking		Push type			
Weight (excluding generator)	kg	114		120	