SMLV400A/B

MANUAL LIFTING MOBILE LIGHTING VEHICLE



FEATURES

- Equipped with imported power, quality assurance, superior performance.
- Equipped with metal halide lamp, large luminous flux and long life.
- High performance self-braking hand winch
- 3-section lifting pole, galvanized light pole, anti-drop, corrosion-resistant.
- Left and right windproof support frame, stable support
- Integrated operator panel
- 5 meters lifting height, adjustable irradiation angle, long irradiation distance

Overall size		
Lay down support frame	mm	1585*1740
Pack up support frame	mm	1250*860
Lighthouse Telescopic	mm	1700-5000
Luminous Flux	lm	72000/144000
Power*Number of lights	w	400*2/400*4

Technical Parameter	Unit	SMLV400A/B			
Model		SMLV400A		SMLV400B	
Generator set					
Gasoline generator		HONDA EC4000CX/LONCIN LC3500			
Diesel generator		ANMAX DG3500CLE			
Extemal contact power supply		Externally accessible			
Name		Single phase alternator			
Frequency	hz	50			
Rated voltage	V	220			
Maximum power	kva	3. 2			
Rated power	kva	3			
Continuously working	hr	13			
Fuel tank capacity	L	25			
Engine weight	kg	68			
Headlights		Metal Halide		LED lamp	
Engine size	mm	590*430*435		590*430*435	
Power*Numberof lights	w	400*2	400*4	200*2	200*4
Luminous flux	lm	72000	144000	56000	112000
Light stand retractable	mm	1700-5000			
Light stand operation		Three-section lift rod			
Lifting method		Hand lift			
Inclination	°	<10			
Wind resistance		<6			
L*W-Lay down support	mm	1585*1740		1585*1740	
L*W-fold support	mm	1250*860		1250*860	
Way of walking		Push type			
Weight (excluding generator)	kg	112		116	