4TN4000

Trailer hand-lifting mobile lighting tower



FEATURES

- Equipped with imported power, quality assurance, superior performance.
- Equipped with metal halide lamp, large luminous flux and long life.
- High performance self-braking hand winch
- Three-section lifting pole, galvanized light pole, anti-drop, corrosion-resistant.
- Five windproof support legs for stable support
- Integrated operator panel with rain cover
- 9 meters lifting height, adjustable irradiation angle, long irradiation distance
- Large capacity fuel tank, long battery life

Overall size		
Total length	mm	4400
Total width	mm	1670
Total height	mm	1830
Height of mast sections	m	9
Tire and rim size	"	14

Technical Date	Unit	4TN4000			
Model		4TN4000			
Engine Brand		CHANGCHAI		YANMAR	KUBOTA
Engine Model		3M78	CZ380Q	3TNV76	D1105
Engine Type		Three cylinder,water-cooled,four stroke			
Power	kw	11.5	14.3	10.7	12.6
Frequency	rpm	1500			
Burning method		E-TVS			
Intake method		Naturally aspirated			
Emission class		Conventional			
Generator standard configuration		XINGNUO			
Rated voltage (50/60hz)	V	230/240-120			
Motor insulation class		CLASS H			
Motor protection class		IP23			
Headlights		Metal Halide Flood Lights		LED lamp	
Luminous flux	lm	440000		224000	
Power & number of lamps	w	1000x4		400x4	
Number of pole sections		3			
Fuel tank capacity	L	90			
Continuous working time	h	80			
Unit start method		Key start			
Maximum wind resistance speed	m/s	20			
Noise level	dB	72 at 7 meters			
Suspension & Brakes		Leaf spring suspension & single axle without brake			
Drawbar		Adjustable lever with retractable adjustable guide wheel			
Maximum lift height	m	9			
Tire size	"	14			
Maximum traction speed	km/h	100			
Length	mm	4400			
Width	mm	1670			
High	mm	1830			
Weight	kg	980			