SVH50

Handheld double drum vibrating roller



FEATURES

- Equipped with famous brand power, quality assurance, superior performance
- Overall spraying, wide field of vision, beautiful and generous
- Small working radius, can work in narrow areas
- Adopt domestic famous brand hydraulic pump, motor, high quality and high stability
- Lengthened armrest, easy to turn, labor-saving
- The transmission adopts Japanese FYH Seiko bearings to ensure the working performance of the whole machine

Overall size		
Overall length	mm	2480
Working width	mm	788
Overall height	mm	1820
Drum diameter	mm	426
Drum width	mm	600
Exciting force	kn	30

Technical parameter	Unit	SVH50		
Model		SVH50	SVH50C	SVH50S
Weight				
Operating weight	kg	530		
Static line load	n/cm	45		
Size				
Full width	mm	780		
Full length (with armrests flat)	mm	2480		
Full height (armrest upright)	mm	1820		
Package dimensions	mm	1300*840*1050		
Drum width	mm	600		
Drum diameter	mm	426		
Start up		Recoil hand pull / electric start		
Drive				
Engine brand		HONDA	CHANGFA/CHANG CHAI/KAMA	CHANGCHAI
Engine model		GX270	178	R180
Engine type		gasoline four-stroke	Diesel four-stroke	Diesel Evaporative Water Cooling
Number of cylinders		1	1	1
Output Power	kw	6. 7	4. 4	5. 7
Rotating speed	rpm	3600	3600	2600
Walking characteristics				
Speed	km/h	0-4		
Theoretical climbing ability	%	30		
Brake				
Way of walking		Two-way hydraulic chain drive		
Vibration system				
Vibrating drum		before + after		
vibration frequency	hz	70		
Vibration amplitude	mm	0. 6		
Exciting force	kn	30		
Sprinkler system				
Form		Gravity shower		------
Capacity				
Fuel capacity	L	5. 9	3. 5	6. 5
Lubricant capacity	L	1. 1	1. 1	2
Hydraulic tank capacity	L	18		
Water tank capacity	L	20	20	------