SVH70

Ride on double drum vibratory roller



FEATURES

- Equipped with famous brand power, quality assurance, superior performance
- Ergonomic streamlined body design, wide field of vision, beautiful appearance
- Imported hydraulic variable pump and quantitative motor, stepless speed change, walking forward and backward
- The control panel is fully functional, one-key operation
- Front-mounted LED headlights can be constructed at night
- Hydraulic oil air cooling fan heater, fast heat dissipation and long battery life
- The product has passed CE certification

Overall size

Overall length	mm	1550
Working width	mm	875
Overall height	mm	1210
Drum diameter	mm	530 front 425 rear
Drum width	mm	700 front 500 rear
Exciting force	kn	30

Technical parameter	Unit	SVH70			
Model		SVH70		SVH70C	
Weight					
Operating weight	kg	620			
Static line load	n/cm	55			
Size					
Working width	mm	875			
The length of the whole machine	mm	1550			
Height of the whole machine	mm	1210			
Outside the turning radius	mm	2300			
Drum width	mm	700 front 500 rear			
Drum diameter	mm	530 front 425 rear			
Wheelbase	mm	1110			
Drive					
Engine brand		HONDA	LONCIN	CHANGFA	CHANGCHAI
Engine model		GX390	390FD	180F	178F
Engine type		gasoline four-stroke	Four-stroke gasoline air-cooled	diesel four-stroke	Air-cooled four-stroke
Number of cylinders		1			
Output Power	kw	9.7	9.7	4.8	4.4
Rotating speed	rpm	3600	2400	3600	3600
Electrical Equipment	V	12			
Drive mode		Two-way hydraulic chain drive			
Walking characteristics					
Speed	km/h	0-6			
Theoretical climbing ability	%	30			
Brake					
Working brake		Variable displacement piston pump			
Turn					
Steering method		Mechanical steering			
Steering system		Rear wheel steering			
Vibration system					
Vibrating drum		front			
Drive form		Mechanical transmission			
Vibration frequency	hz	70			
Vibration amplitude	mm	0.5			
Exciting force	kn	30			
Sprinkler system					
Form		Gravity shower			
Capacity					
Hydraulic oil capacity	L	12			
Fuel capacity	L	6.5	6.5	3.5	2.7
Water tank capacity	L	18			